

ML-7H

LCD Monitor

Product description

The ML-7H monitors are LCD monitor specifically designed for video surveillance applications where a small monitor is required. They are suitable for mounting on bracket or flush mounting and are ideal for installation on vehicles.

Package Contents

- Monitor-based collection and bracket
- for cable connections
- Infrared remote control
- sun protection

compatible cameras

The monitor is compatible with all analog cameras in traditional CVBS format. In addition you can also connect analog cameras into high resolution AHD 720P and 1080P.

Connections

The monitor is provided with a connecting cable to connect to the connector that protrudes from the monitor itself.

At the other end of the cable connects the 12VDC power supply (to the black cable connects the negative and the red positive).

The monitor is equipped with 3 female RCA video inputs for connecting max. 3 cameras. The monitor can show a single screen camera at a time, which can be selected with the front panel.

There are also 3 colored cables (one per channel). Each of these, if connected to positive 12VDC brings full-screen on the corresponding channel monitor. This is useful to change the shot without pressing any button; for example, when switching from normal driving to the reverse. In vehicles the 12VDC signal can be taken from the middle of the unit.

front button panel

1. Brightness - (minus key)
2. Menu
3. Brightness + (plus key)
4. Power button
5. Channel 1
6. Channel 2
7. Channel 3

Using the Monitor

Press the power button (4) to turn the monitor. Press the CH1 / CH2 / CH3 (5/6/7) to view the video input 1, 2 or 3. Press the MENU button (2) to enter the programming.

Configuration Menu

Press the MENU button to access the programming menu. The factory-set language is English. And 'possible to select the Italian language by pressing 2 times the menu key and 6 times the + button.

Use these buttons:

MENU: Allows you to access the menu and browse programming sections

CH1 / CH2 / CH3: once sectioned the desired section, pressing the channel button on which there is located you can scroll through the entries

KEYS +/-: to select a section of the menu and to change a parameter

In the programming menu you can set the BRIGHTNESS, CONTRAST, SATURATION, the FLIP (FEATURE ROLLOVER IMAGE / MIRROR), the LANGUAGE and reset the factory settings in the RESET using the +/- buttons

Bracket

The special jointed bracket of ML-7H monitor allows mounting on any surface without the need for additional accessories.

If necessary, it is possible to remove the bracket if you prefer flush mounting surface.

